








REVERSIBLE TILT DITCHING BUCKETS

- Entirely made of **Hardox® 450 steel**. Lighter and more durable than commercial steel.
- 90-degree pivot angle (45 degrees on each side). Increases operating versatility regardless of the excavator's position and reduces the support staff required.
- The **reversible Cotech ears** enables front digging under obstacles or near building foundations.
- Hydraulic cylinders and central pivot axis mounted on greasable bushings for superior operating precision.
- Compatible with the majority of excavator manufacturers and models.





| Reversible Cotech Ears | | | | | | | |
|------------------------|--|--|--|--|--|--|--|
| | | | | | | | |

| Technical Specifications | | | | | | |
|--------------------------|--------------------|--------|-------|-----------|------------------|--|
| Model | Bucket Capacity | Height | Width | Weight | Excavator Weight | |
| EGFI1R-1230-C | 0.06 yd³ | 12" | 30" | 140 lbs | 1 to 1.9 tons | |
| EGFI2R-1536-C | 0.12 yd³ | 15" | 36" | 296 lbs | 2 to 2.9 tons | |
| EGFI3R-1736-C | 0.15 yd³ | 17" | 36" | 384 lbs | 3 to 3.8 tons | |
| EGFI3R-1942-C | 0.21 yd³ | 19" | 42" | 525 lbs | 3.9 to 4.9 tons | |
| EGFI3R-2248-C | 0,35 yd³ | 22" | 48" | 615 lbs | 5 to 7 tons | |
| EGFI4R-2448-C | 0.38 yd³ | 24" | 48" | 847 lbs | 7 to 10 tons | |
| EGFI4R-2454-C | 0.43 yd³ | 24" | 54" | 914 lbs | 7 to 10 tons | |
| EGFI4R-2460-C | 0.48 yd³ | 24" | 60" | 980 lbs | 7 to 10 tons | |
| EGFI5R-3260-C | 0.87 yd³ | 32" | 60" | 1,712 lbs | 10 to 16 tons | |
| EGFI6R-4072-C | 1.68 yd³ | 40" | 72" | 2,811 lbs | 17 to 27 tons | |



